



TEGERA® 9181

Anti-vibration glove, unlined, full grain goatskin of top quality, Vibrothan®, Cat. II, black, yellow, reinforced index finger, reinforced seams, Velcro®, for heavy work

PROPERTIES

Very durable, comfortable

SPECIFICATION

TYPE OF GLOVE Anti-vibration gloves

CATEGORY Cat. II

SIZE RANGE 9, 10, 11

PALM MATERIAL Full grain goatskin of top quality, Vibrothan®

BACK MATERIAL Full grain goatskin of top quality

LINING Unlined

FASTENING Velcro®

LENGTH RANGE 240-260 mm

COLOUR Black, yellow

PIECES PER PACKAGE/CARTON 1/36

DISPLAY No thread

MATERIAL SPECIFICATION Leather, natural latex

1(3)

VIBROTHAN®

SIZE	ART. NO.	EAN NO.
9	9181-9	7392626059351
10	9181-10	7392626055919
11	9181-11	7392626055926

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 9181

FEATURES

Vibration-reducing according to EN ISO 10819, reinforced index finger, padded palm, pre-curved fingers, short model

PRIMARY PROTECTION

Prevents risk of: vibration injuries

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY INDUSTRIES OF USE


Mining, machinery and equipment, MRO, automotive, building and construction

TYPE OF WORK

Heavy weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-06-10

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 9181

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	2	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	1	(4)


EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN ISO 10819:1997 Mechanical vibration and shock



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2015-06-10

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com