



TECHNICAL SHEET FA 30 1000 20

ENERGY ABSORBING STRETCHING LANYARD



- Energy absorber in webbing with central weaving with progressive deformation, which reduces the impact of the fall to less than 6 kN.
- Energy absorber equipped with a fall indicator:



- Protective 45 mm wide Polyester expandable / elasticated webbing lanyard.
- Expanded length: 2 m.
- Relaxed length: 1.4 m.

Connectors:

1 aluminium screw-locking karabiner, opening 22 mm (FA 50 105 22B) et 2 aluminium rebar hook, opening 60 mm (FA 50 218 60).

Compliance: EN355:2002, and tested as per VG11 of PPE Directive 89/686/EEC.

Material of components:

Lanyard: Polyester

Absorber: Polyester and Polyamide

Connectors : Aluminium

Size :	CE	Weight :
2 m		1.8 kg

KRATOS SAFETY

ZI les Portes du Dauphiné
4, rue de l'Aigue
69780 Saint Pierre de Chandieu – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE
5609 00 90
CARTON SIZE / PIECES
60 x 40 x 24 cm / 10
AET N° 4345 I 6 E 3
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
ARTICLE 11 GB07/73551
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom