



TECHNICAL SHEET FA 30 307 20

DIELECTRIC ENERGY ABSORBING WEBBING LANYARD

Dielectri



Energy absorbing lanyard designed to protect the operators working in an environment with potential electrical hazards.

- Energy absorber in 44 mm wide webbing, which reduces the impact of fall to less than 6kN. Energy absorber equipped with a fall indicator. Has a black protective sleeve for increased longevity and UV-resistance.
- 30 mm wide polyester webbing.

Connectors:

One textile loop at one end for attachment to the dorsal D-ring of the harness, and one dielectric rebar hook FA 50 222 55 at the other end.



Compliance : EN355 : 2002.

Material of components:

Strap: Polyester.

Absorber: Polyester and Polyamide.

Connector: Steel with a polymer composite that can withstand a maximal voltage of 14kV.

Length:	CE	Weight:
1.80 m		1.06 kg

KRATOS SAFETY

ZI les Portes du Dauphiné
4, rue de l'Aigüe
69780 Saint Pierre de Chandieu – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

6307 90 98

CARTON SIZE / PIECES

60 x 40 x 24 cm / 20

AET N°4303 I6 E1

Satra Technology Centre, N°0321

Wyndham Way, Telford Way, Kettering
Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom