



## TECHNICAL SHEET FA 30 404 15

### FORKED DIELECTRIC ENERGY ABSORBING WEBBING LANYARD

**Dielectri**



Forked energy absorbing lanyard designed to protect the operators working in an environment with potential electrical hazards.

- Energy absorber in 44 mm wide webbing, which reduces the impact of fall to less than 6kN. Energy absorber equipped with a fall indicator. Has a black protective sleeve for increased longevity and UV-resistance.
- 30 mm wide polyester webbing.

#### Connectors:

One textile loop at one end for attachment to the dorsal D-ring of the harness, and two dielectric rebar hooks FA 50 222 55 at the other end of each lanyard.



**Compliance :** EN355 : 2002.

#### Material of components:

Strap: Polyester.

Absorber: Polyester and Polyamide.

Connector: Steel with a polymer composite that can withstand a maximal voltage of 14kV.

<b>Length:</b>	<b>CE</b>	<b>Weight:</b>
1.50 m		1.59 kg

#### KRATOS SAFETY

ZI les Portes du Dauphiné  
4, rue de l'Aigüe  
69780 Saint Pierre de Chandieu – FRANCE

Tel. : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

[www.kratossafety.com](http://www.kratossafety.com) / [info@kratossafety.com](mailto:info@kratossafety.com)

#### HS CODE

6307 90 98

#### CARTON SIZE / PIECES

60 x 40 x 24 cm / 20

AET N°4302 16 E2

#### Satra Technology Centre, N°0321

Wyndham Way, Telford Way, Kettering  
Northamptonshire, NN16 8SD, United Kingdom

#### ARTICLE 11 GB07/73551

#### SGS United Kingdom Ltd., N°0120

Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom