






In LOCK



HS CODE
83081000
CARTON SIZE / PCS.
60 x 40 x 24 cm / 30
AET (UE) N° (in progress)
<b>DOLOMITICERT, n°2008</b> Zona Industriale Villanova 32013 LONGARONE (BL) - Italia
MODULE D 11 IN14/14003
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 60 018 00
CE	EN 795:2012 Type B
	x1
MAT.	
R (kN) / MBS (kN)	12 kN / 15 kN
	--- Ø 18-19 mm x 110 mm (concrete)
	0.15 KG



R (kN) / MBS (kN)

**Nombre d'utilisateurs**

Number of users

**Cantidad de usuarios**

Quantità di utilizzatori

**Anzahl der Benutzer**

(concrete)

**Béton**

Concrete

**Hormigón**

Concreto

**Beton**


**Résistance statique (en kN) / Résistance à la rupture**

Static strength / Minimum Breaking Strength

**Resistencia estática (en kN) / Resistencia a la ruptura (en kN)**

Resistenza statica (in kN) / Resistenza alla rottura (in kN)

**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**



**Fixations à utiliser / Dimensions de la structure d'accueil**

Fasteners to use / Dimensions of the receiving structure

**Fijaciones que deben usarse / Dimensiones de la estructura receptora**

Elementi di fissaggio da utilizzare / Dimensioni della struttura ospitante

**Zu verwendende Befestigungen / Abmessungen der Aufnahmestruktur**